

SPECIFICATIONS

2019 MULE PRO-MX™ EPS LE



POWER

Engine	4-stroke, single-cylinder, SOHC, 4-valve, liquid-cooled
Displacement	695cc
Maximum Torque	42.7 lb-ft @ 5000 rpm
Fuel System	DFI® with 44mm throttle body
Transmission	Continuously Variable Transmission (CVT) with centrifugal clutch, (H,L,N,R)
Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock
Engine Braking	Yes
Alternator Output (max)	35.7 amp

CAPABILITY

Steering	Electric Power Steering (EPS) / rack-and-pinion
Ground Clearance	10.6 in
Fuel Capacity	9.5 gal
Turning Radius	14.0 ft
Cargo Bed Dimensions (LxWxH)	33.4 x 44.1 x 9.1 in
Cargo Bed Capacity	700 lb (600 lb California models)
Load Capacity	1200 lb
Seating Capacity	2
Towing Capacity	1500 lb
Lighting	(2) Halogen (high/low beam) headlights and (2) LED headlights (high/low beam)

DETAILS

Overall Length	110.0 in
Overall Width	60.0 in
Overall Height	74.4 in (EPS) / 75.8 (EPS LE, EPS Camo)
Curb Weight	1587.6 lb (EPS) / 1594.2 (EPS LE) / 1598.6 (EPS Camo)**
Wheelbase	78.9 in
Instruments	Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt reminder lamps
Color Choices	Firecracker Red
Warranty	Kawasaki Strong 3-Year Limited Warranty
Kawasaki Protection Plus™ (optional)	12, 24 or 36 months

**Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

KAWASAKI.COM

Kawasaki